

## Product information

# Deco Effect Paste

772118.2

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.



Delta 32, 6825 MS Arnhem  
T +31 (0) 26 388 21 02  
F +31 (0) 26 364 41 51  
Email: [info@plantag.nl](mailto:info@plantag.nl)  
Website: [www.plantag.nl](http://www.plantag.nl)

## Product

Deco Effect Paste is a water-dilutable effect paste that can be applied to various lacquer systems.

## Product description

Fast and easy applicable effect paste for a decorative note of the wood grain. After applying and drying, the Deco Effect paste must be coated with a transparent lacquer.

## Field of application

For the wood, furniture and carpentry industrie.

## Technical data

Color	White
Gloss	not applicable
Mixing ratio	ready for use
Thinner	Water, SO 602000
Delivery viscosity	Ca. 20-45 sec.
Spray viscosity	20-45 sec.
Potlife	not applicable
Solid contents	Ca. 32,4 %
Storage stability	Stored in original unopened packaging for 6 months in a cool, frost-free place.



# Deco Effect Paste

772118.2

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.

## Application

Application method	apply with cloth, brush or spray
Layers	depends on required effect
Yield per layer	depends on required effect
Optimal temp. working space	16-18 °C (do not use under 15 °C )
Optimal humidity	60 %
Material temperature	16-20 °C
Cleaning Thinner	Water SO 602000
Pre-treatment of wood	P 320
Suitable on bleached wood	Not applicable
UV resistance	-
Optimal moisture content wood	12-14 %
Drying times	15 min. at 20 °C when applied a thin layer. 60 min. at 20 °C sandable Forced drying will reduce the drying time.

## Disposal

Treat waste from paints or oil as chemical waste dispose of as chemical waste.

## Package

Available in 5, 10 or 25 Kg cans

## Safety, Standards and durability

No ADR  
Info: Safety data sheet.

