

## Product

Adhesive primer for metal 262150

## Product description

Special 1 component primer for various metals on base from phenol resins and polyvinylbutyral.

## Field of application

Fast drying 1K adhesive primer for various metals such as steel, aluminum and zinc based on phenolic resins and polyvinylbutyral. Test adhesion beforehand.

## Technical data

Colour	Transparent, white and grey
Gloss	not applicable
Mixing ratio	Not applicable
Thinner	SO 662263
Delivery viscosity	55-65 Sec.
Spray viscosity	20-65 Sec
Potlife	Not applicable
Solid contents	32
Storage stability	In original unopened packaging 12 months in a cool, dry and frost-free place.

## Application

Application method	Spraying
--------------------	----------

Layers	1
Yield per layer	70-100 gr/m
Maximum Yield	120 gr/m
Optimal temp. spray area	16-18 C <sup>0</sup>
Optimal humidity	60%
Material temperature	16-20 C <sup>0</sup>
Cleaning Thinner	602020
Pretreatment of wood	P 120
Suitable on bleached wood	not applicable
UV resistance	not applicable
Ground lack sanding	P 320.
Optimal moisture content wood	12-14 %.
Drying times	min 1 hour

## Disposal

Treat waste from paints as chemical waste.  
dispose of as chemical waste.

## Packing

5, 10 kg cans.

## Safety, Standards and Durability

UN Code 1263, paint, 3, VG II, (D/E) , GGVS / ADR

Info                      Safety data sheet

