

# Water stain

## BP 710xxxx

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.

Delta 32, 6825 MS Arnhem  
T +31 (0) 26 388 21 02  
F +31 (0) 26 364 41 51  
Email: [info@plantag.nl](mailto:info@plantag.nl)  
Website: [www.plantag.nl](http://www.plantag.nl)

## Product

Water stain BP 710-XXXX, available in various trendy colours.

## Product description

The water stain BP 710-XXXX very nice and easily workable stain with a nice coloring of the wood.

## Field of application

Carpentry and furniture industry.

## Technical data

Colour	Aavailable in various trendy colors
Gloss	Does not apply
Mixing ratio	Does not apply
Thinner	Do not use thinner.
Delivery viscosity	12-14 sec
Spray viscosity	12-14 sec
Potlife	Does not apply
Solid contents	Ca. 2 %
Storage stability	Stored in original unopened packaging for 12 months in a cool, frost-free place.

# Water stain

## BP 710xxxx

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.

Delta 32, 6825 MS Arnhem  
T +31 (0) 26 388 21 02  
F +31 (0) 26 364 41 51  
Email: [info@plantag.nl](mailto:info@plantag.nl)  
Website: [www.plantag.nl](http://www.plantag.nl)

## Application

Application method	Spray
Layers	1
Yield per layer	10-30 gr/ m <sup>2</sup>
Optimal temp. working space	16-18 °C
Optimal humidity	60 %
Material temperature	16-20 C°
Cleaning Thinner	Water
Pre-treatment of wood	P 120
?Suitable on bleached wood	Does not apply
Sanding of lacker	P 320
Optimal moisture content wood	12-14 %.
Drying times	2-4 hours at 20°C. Forced drying will reduce the drying time.

## Disposal

Treat waste from paints or oil as chemical waste dispose of as chemical waste.

## Package

Available in several packages (5, 10 or 25 Kg cans).

## Safety, Standards and durability

UN Code	NO ADR.
Info	Safety data sheet

